

LAMOILLE COUNTY SEPTIC SYSTEM RATING CLASSES

1/2/97

MAP SYMBOL	MAP UNIT NAME	CLASS	FOOT NOTE
AdB	ADAMS LOAMY FINE SAND, 2 TO 8 PERCENT SLOPES	1	
AdC	ADAMS LOAMY FINE SAND, 8 TO 15 PERCENT SLOPES	1	
AdD	ADAMS LOAMY FINE SAND, 15 TO 25 PERCENT SLOPES	1	b
AdE	ADAMS LOAMY FINE SAND, 25 TO 50 PERCENT SLOPES	1	b
AeC	ADAMS-ADAMS VARIANT LOAMY FINE SANDS, ROCKY, 8 TO 15 PERCENT SLOPES	3	a
AeD	ADAMS-ADAMS VARIANT LOAMY FINE SANDS, ROCKY, 15 TO 25 PERCENT SLOPES	3	a, c
AeE	ADAMS-ADAMS VARIANT LOAMY FINE SANDS, ROCKY, 25 TO 50 PERCENT SLOPES	6	
AgB	ALLAGASH VERY FINE SANDY LOAM, 2 TO 8 PERCENT SLOPES	1	
BeB	BERKSHIRE FINE SANDY LOAM, 3 TO 8 PERCENT SLOPES	2	
BeC	BERKSHIRE FINE SANDY LOAM, 8 TO 15 PERCENT SLOPES	2	
BeD	BERKSHIRE FINE SANDY LOAM, 15 TO 25 PERCENT SLOPES	2	b
BkB	BERKSHIRE VERY STONY FINE SANDY LOAM, 3 TO 8 PERCENT SLOPES	2	
BkC	BERKSHIRE VERY STONY FINE SANDY LOAM, 8 TO 15 PERCENT SLOPES	2	
BkD	BERKSHIRE VERY STONY FINE SANDY LOAM, 15 TO 25 PERCENT SLOPES	2	b
BrB	BERKSHIRE-TUNBRIDGE FINE SANDY LOAMS, ROCKY, 3 TO 8 PERCENT SLOPES	3	a
BrC	BERKSHIRE-TUNBRIDGE FINE SANDY LOAMS, ROCKY, 8 TO 15 PERCENT SLOPES	3	a
BrD	BERKSHIRE-TUNBRIDGE FINE SANDY LOAMS, ROCKY, 15 TO 25 PERCENT SLOPES	3	a, c
BtE	BERKSHIRE AND MARLOW SOILS, 25 TO 50 PERCENT SLOPES	6	
BuB	BOOTHBAY SILT LOAM, 3 TO 8 PERCENT SLOPES	4	
BuC	BOOTHBAY SILT LOAM, 8 TO 15 PERCENT SLOPES	4	
BuD	BOOTHBAY SILT LOAM, 15 TO 25 PERCENT SLOPES	4	c
Bx	BOROHEMISTS, DEEP	7	
By	BOROHEMISTS, MODERATELY DEEP OVER LOAMY SUBSTRATUM	7	
CoB	COLTON-DUXBURY COMPLEX, 2 TO 8 PERCENT SLOPES	1	
CoC	COLTON-DUXBURY COMPLEX, 8 TO 15 PERCENT SLOPES	1	
CoD	COLTON-DUXBURY COMPLEX, 15 TO 25 PERCENT SLOPES	1	b
CoE	COLTON-DUXBURY COMPLEX, 25 TO 50 PERCENT SLOPES	1	b
CrB	CROGHAN LOAMY FINE SAND, 2 TO 8 PERCENT SLOPES	4	
FrB	FRAGIAQUEPTS AND HAPLAQUEPTS, 0 TO 8 PERCENT SLOPES	7	
Ha	HAMLIN SILT LOAM	6	
Hs	HISTIC FLUVAQUENTS, FREQUENTLY FLOODED	7	
Le	LIMERICK VARIANT SILT LOAM	6	

FOOTNOTES - see text

a - Areas with bedrock at less than 24 inches are not suitable.

b - This map unit has a slope limitation requiring site modification.

c - Areas with slope greater than 20 % are not suitable.

LAMOILLE COUNTY SEPTIC SYSTEM RATING CLASSES

1/2/97

MAP SYMBOL	MAP UNIT NAME	CLASS	FOOT NOTE
LoE	LONDONDERRY-STRATTON COMPLEX, 25 TO 60 PERCENT SLOPES	6	
LyB	LYMAN-TUNBRIDGE FINE SANDY LOAMS, VERY ROCKY, 3 TO 8 PERCENT SLOPES	5	a
LyC	LYMAN-TUNBRIDGE FINE SANDY LOAMS, VERY ROCKY, 8 TO 15 PERCENT SLOPES	5	a
LyD	LYMAN-TUNBRIDGE FINE SANDY LOAMS, VERY ROCKY, 15 TO 25 PERCENT SLOPES	5	a, c
LyE	LYMAN-TUNBRIDGE FINE SANDY LOAMS, VERY ROCKY, 25 TO 60 PERCENT SLOPES	6	
MaB	MARLOW FINE SANDY LOAM, 3 TO 8 PERCENT SLOPES	3	
MaC	MARLOW FINE SANDY LOAM, 8 TO 15 PERCENT SLOPES	3	
MaD	MARLOW FINE SANDY LOAM, 15 TO 25 PERCENT SLOPES	3	c
MrB	MARLOW VERY STONY FINE SANDY LOAM, 3 TO 8 PERCENT SLOPES	3	
MrC	MARLOW VERY STONY FINE SANDY LOAM, 8 TO 15 PERCENT SLOPES	3	
MrD	MARLOW VERY STONY FINE SANDY LOAM, 15 TO 25 PERCENT SLOPES	3	c
On	ONDAWA FINE SANDY LOAM	6	
PaA	PEACHAM STONY MUCK, 0 TO 5 PERCENT SLOPES	6	
PeB	PERU FINE SANDY LOAM, 3 TO 8 PERCENT SLOPES	4	
PeC	PERU FINE SANDY LOAM, 8 TO 15 PERCENT SLOPES	4	
PeD	PERU FINE SANDY LOAM, 15 TO 25 PERCENT SLOPES	4	c
PfB	PERU VERY STONY FINE SANDY LOAM, 3 TO 8 PERCENT SLOPES	4	
PfC	PERU VERY STONY FINE SANDY LOAM, 8 TO 15 PERCENT SLOPES	4	
PfD	PERU VERY STONY FINE SANDY LOAM, 15 TO 25 PERCENT SLOPES	4	c
Po	PODUNK FINE SANDY LOAM	6	
PtB	POTSDAM SILT LOAM, 3 TO 8 PERCENT SLOPES	3	
PtC	POTSDAM SILT LOAM, 8 TO 15 PERCENT SLOPES	3	
PtD	POTSDAM SILT LOAM, 15 TO 25 PERCENT SLOPES	3	c
RkE	RICKER PEAT, VERY ROCKY, 15 TO 80 PERCENT SLOPES	6	
Ru	RUMNEY FINE SANDY LOAM	6	
SaB	SALMON VERY FINE SANDY LOAM, 3 TO 8 PERCENT SLOPES	2	
SaB2	SALMON VERY FINE SANDY LOAM, 3 TO 8 PERCENT SLOPES, ERODED	2	
SaC	SALMON VERY FINE SANDY LOAM, 8 TO 15 PERCENT SLOPES	2	
SaC2	SALMON VERY FINE SANDY LOAM, 8 TO 15 PERCENT SLOPES, ERODED	2	
SaD	SALMON VERY FINE SANDY LOAM, 15 TO 25 PERCENT SLOPES	2	b
SaD2	SALMON VERY FINE SANDY LOAM, 15 TO 25 PERCENT SLOPES, ERODED	2	b
SaE2	SALMON VERY FINE SANDY LOAM, 25 TO 50 PERCENT SLOPES, ERODED	6	

FOOTNOTES - see text

a - Areas with bedrock at less than 24 inches are not suitable.

b - This map unit has a slope limitation requiring site modification.

c - Areas with slope greater than 20 % are not suitable.

LAMOILLE COUNTY SEPTIC SYSTEM RATING CLASSES

1/2/97

MAP SYMBOL	MAP UNIT NAME	CLASS	FOOT NOTE
SdC	SALMON VARIANT-SALMON VERY FINE SANDY LOAMS, ROCKY, 8 TO 15 PERCENT SLOPES	3	a
SdD	SALMON VARIANT-SALMON VERY FINE SANDY LOAMS, ROCKY, 15 TO 25 PERCENT SLOPES	3	a, c
SdE	SALMON VARIANT-SALMON VERY FINE SANDY LOAMS, ROCKY, 25 TO 50 PERCENT SLOPES	6	
SeD	SCANTIC VARIANT BOULDERY SILT LOAM, 8 TO 25 PERCENT SLOPES	4	c
SeE	SCANTIC VARIANT BOULDERY SILT LOAM, 25 TO 50 PERCENT SLOPES	6	
Sr	SEARSPORT MUCK	6	
StC	STRATTON-LONDONDERRY COMPLEX, 8 TO 25 PERCENT SLOPES	6	
SwA	SWANVILLE SILT LOAM, 0 TO 6 PERCENT SLOPES	6	
Te	TEEL SILT LOAM	6	
TuB	TUNBRIDGE-LYMAN FINE SANDY LOAMS, ROCKY, 3 TO 8 PERCENT SLOPES	5	a
TuC	TUNBRIDGE-LYMAN FINE SANDY LOAMS, ROCKY, 8 TO 15 PERCENT SLOPES	5	a
TuD	TUNBRIDGE-LYMAN FINE SANDY LOAMS, ROCKY, 15 TO 25 PERCENT SLOPES	5	a, c
TuE	TUNBRIDGE-LYMAN FINE SANDY LOAMS, ROCKY, 25 TO 60 PERCENT SLOPES	6	
Ud	UDIFLUVENTS, FREQUENTLY FLOODED	7	
W	WATER, LESS THAN 40 ACRES	7	
WaA	WALPOLE FINE SANDY LOAM, 0 TO 6 PERCENT SLOPES	6	

FOOTNOTES - see text

- a - Areas with bedrock at less than 24 inches are not suitable.
- b - This map unit has a slope limitation requiring site modification.
- c - Areas with slope greater than 20 % are not suitable.